

# VieTape SI3604

# **POLYIMIDE TAPE**


# **DESCRIPTION**

Vietape SI3604 is a polyimide tape with silicone adhesive used for PCB solder masking and other high temperature applications. This product is amber colored with 0.06mm thickness.

# **APPLICATIONS**

- o Protection of gold fingers of printed circuit boards during soldering process
- o Release surface in fabrication of parts cured at elevated temperatures.
- o General electrical purpose and manual wiring harness

# **STRUCTURE**



#### **PERFORMANCE**

Properties	Value
Adhesive	Silicone
Backing	Polyimide Film
Color	Amber
Adhesion strength (peel off 90 ° )	6N/25mm
Tensile Strength at Break	115N/25mm
Elongation at Break	50%
Backing Thickness	0.025 mm
Total Tape Thickness	0.06 mm
Temperature Use Range	-70° to 260°C
Dielectric Strength	4500 volts
Flame Retardant	Meet UL510

Standard conditions of test location at 23°C, 50%

Issue date: September 2022

VIETAPE MATERIAL TECHNOLOGY CO., LTD



# **Technical Data Sheet**



# VieTape SI3604 POLYIMIDE TAPE

# **DIRECTION OF USE**

Temperatures between 21 and 38°C are ideal for application.

For greater substrate contact, pressure-sensitive adhesives use viscous flow. Better adhesive contact is created by applying firm application pressure, which also strengthens the bond. For operation at low temperatures, this is particularly crucial.

The bonding surfaces must be thoroughly united, clean, and dry in order to achieve the best adhesion. Typical surface cleaning solvents are isopropyl alcohol/water mixture (rubbing alcohol) or heptane. Please take the appropriate precautions to handle solvents safely.

# **SHELF LIFE**

12 months from date of manufacture when stored at 27°C to 35 °C and 60% relative humidity.

The above values are sample observed values, we do not guarantee the actual performance due to the different of application method, bonding design, bonding substrate. We highly recommend customer to test in the real part

Issue date: September 2022

