



VieTape KP7100 KRAFT PAPER TAPE

DESCRIPTION

Vietape KP7100 is a high-strength, conformable tape with kraft paper backing coated with acrylic adhesive. This tape provides good adhesion to most surfaces and is ideal for packaging applications.

APPLICATION

- Carton box sealing and packaging.
- Goods packaging and preservation during transportation
- Marking or taking note, decoration.

STRUCTURE



PERFORMANCE

Properties	Value
Color	Brown
Backing	Kraft paper
Adhesive	Acrylic
Total thickness	0.13mm
Length, Width	50M, Optional
Tolerance	10%
Adhesion to steel (180°)	10N/25mm
Working temperature	- 40 - 100°C

Issue date: September 2022

VIETAPE MATERIAL TECHNOLOGY CO., LTD





Technical Data Sheet

VieTape KP7100 KRAFT PAPER TAPE

DIRECTION OF USE

Temperatures between 21 and 38°C are ideal for application.

For greater substrate contact, pressure-sensitive adhesives use viscous flow. Better adhesive contact is created by applying firm application pressure, which also strengthens the bond. For operation at low temperatures, this is particularly crucial.

The bonding surfaces must be thoroughly united, clean, and dry in order to achieve the best adhesion. Typical surface cleaning solvents are isopropyl alcohol/water mixture (rubbing alcohol) or heptane. Please take the appropriate precautions to handle solvents safely.

SHELF LIFE

Store in original package at room temperature (27-35°C) and 60% relative humidity, avoid direct sunlight.

Shelf life is 12 months from date of manufacture when store at recommended storage condition.

The above values are sample observed values, we do not guarantee the actual performance due to the different of application method, bonding design, bonding substrate. We highly recommend customer to test in the real part

Issue date: September 2022

Technical Data Sheet

VIETAPE MATERIAL TECHNOLOGY CO., LTD

