

VieTape WP7101

WASHI PAPER TAPE

DESCRIPTION

VietTape WP7101 is a versatile yellow masking tape designed for a variety of applications. Its flat paper backing and synthetic adhesive make it ideal for holding, bundling, sealing, and, most notably, masking areas during painting, especially in outdoor environments where prolonged exposure to sunlight is a factor.


APPLICATIONS

General purpose from bonding, bunding, holding and light duty masking.

Can be used widely in almost industries from appliances automotives, electronics,..

Typical applications: automotive decoration &body painting, bunding and fixing for appliances internal wires such as refrigerator and washing machine.

STRUCTURE



PERFORMANCE

Item	Parameter
Color	Blue, Red
Tape thickness	0.1mm
Thickness tolerance	± 10%
Adhesive type	PSA Acrylic
Backing	Washi paper
Tensile Strength	30 (N/25mm)
Elongation	10 %
Adhesion to steel	3.0(N/25mm)
Long Term temperature resistance	90°C
Short Term temperature resistance	Up to 140°C

VIETAPE MATERIAL TECHNOLOGY CO., LTD





Technical Data Sheet

VieTape WP7101

WASHI PAPER TAPE

DIRECTION OF USE

Temperatures between 21 and 30°C are ideal for application.

For greater substrate contact, pressure-sensitive adhesives use viscous flow. Better adhesive contact is created by applying firm application pressure, which also strengthens the bond. For operation at low temperatures, this is particularly crucial.

The bonding surfaces must be thoroughly united, clean, and dry in order to achieve the best adhesion. Typical surface cleaning solvents are isopropyl alcohol/water mixture (rubbing alcohol) or heptane. Please take the appropriate precautions to handle solvents safely.

SHELF LIFE

12 months from date of manufacture when stored at $10 - 30^{\circ}$ C and 0 - 75% relative humidity. The optimal storage conditions are 22°C and 50% relative humidity.

The above values are sample observed values, we do not guarantee the actual performance due to the different of application method, bonding design, bonding substrate. We highly recommend customer to test in the real part

